

DOT Cylinder Valves for Vapor Withdrawal Up to 40 Lbs. LPG Capacity (OPDQ)



Purge Time: Using the industry standard NPGA 133-89a five step purge procedure, *OPDQ* purges in two minutes or less.

BTU Output: *OPDQ* delivers BTU output in excess of other devices, without limiting efficiency of high flow appliances.

Performance Features:

- Quick streamlined configuration ensures optimum performance.
- Quick, easy installation.
- Unique design ensures fast and efficient fills with no premature shut off.
- Teflon coated stem design to avoid hand-wheel sticking.

Pressure (psig)	CFM Propane	BTU
10	2.70	408,240
30	5.30	801,360
50	8.20	1,239,840
70	11.39	1,722,168
90	14.60	2,207,520
110	17.30	2,615,760

Sherwood OPDQ Part Numbers

Size (pounds)	Material	Cylinder ID	Water Capacity	Sherwood Part No.	Sherwood Dip Tube Length
4.25	Steel	8.9	10.2	PVE3349PDLG-408	3.3
5	Steel	8.0	11.9	PVE3349PDLG-408	3.3
5	Steel	7.8	11.9	PVE3349PDLG-408	3.3
5	Steel	7.5	15.5	PVE3349PDLG-408	3.3
10	Steel	8.9	26.1	PVE3349PDLG-407	3.6
11	Steel	8.9	26.2	PVE3349PDLG-407	3.6
11	Steel	12.0	26.2	PVE3349PDLG-408	3.3
11.5	Steel	12.0	27.3	PVE3349PDLG-408	3.3
20	Steel	12.0	47.6	PVE3349PDLG-402	4.0
25	Steel	12.0	59.7	PVE3349PDLG-404	4.8
30	Steel	12.0	71.5	PVE3349PDLG-404	4.8
40	Steel	12.0	95.3	PVE3349PDLG-406	6.5
6	Aluminum	6.0	15.0	PVE3349PDLG-404	4.8
10	Aluminum	10.0	23.6	PVE3349PDLG-402	4.0
20	Aluminum	12.0	47.6	PVE3349PDLG-404	4.8
30	Aluminum	12.0	71.5	PVE3349PDLG-434	6.0
40	Aluminum	12.0	95.2	PVE3349PDLG-435	7.0
20-Strugis	Steel-Type II	12.0	47.6	PVE3329PDQLG-422	4.0
20-Hansen	Steel-Type II	12.0	47.6	PVE3329PDQHLG-424	4.0